

MODEL **TWIN RBL**4000 LITHIUM

POWER UNIT FOR AIRCRAFT AND COMBAT VEHICLES



SUPPLIED WITH UNIT	
2 x Charger	
Output Cable	
Parallel Joining Cable	
2 x Thermal Protection Bag	

OPTIONAL EXTRAS
Twin Trolley
Various output cable lengths
Croc Clips
Various Connectors
25A, 50A, 75A or 100A 28V DC power supply
Carry Case Available

	TWIN RBL4000
Max amps	3000 (Nom. short circuit current) 8000 (Max. short circuit current)
Capacity	56 Amp Hrs @ 10 hr rate
Max Voltage	28V DC
Size (cm)	2 X L 35 x W 10 x H 38
Weight kg	23.2
Operating Temp.	-40°C - +60°C
Case	Aluminum
Voltage indictication	Digital to IP65
Auxiliary Protection	Circuit breaker 40A
Output Cable	2m heavy duty cable with aircraft
	connector
Charger	2 X 4 A Electronic universal AC input.

- · Totally weather protected.
- · Air transportable, 'Non Hazardous'
- · Maintenance free.
- · Tough and compact.
- · No memory effect.
- · Works in any orientation.
- · High charge retention.
- · Long shelf life.
- · Fast recharge.
- · External charger for prolonged unit life.
- · No cycling.
- · Leak proof.
- · Cells replaceable on condition.
- Heavy duty engine starting of turbo prop, turbine, aircraft and helicopters.
- · Starts Main Battle Tanks.
- · Starts Armoured Fighting Vehicles.
- · Lightweight portable start power at remote locations.