



**REDBOX**  
INTERNATIONAL

# RBL2500 14/28

## MODEL **RBL2500** 14/28

**HAND / AIR PORTABLE POWER UNIT FOR AIRCRAFT AND COMBAT VEHICLES**

The RBL2500 14/28 is a switchable unit that can be changed between 14V and 28V settings. This tough and compact unit has exceptional power to weight ratio.



### SUPPLIED WITH UNIT

|              |
|--------------|
| Charger      |
| Output Cable |
| Carry Bag    |

### OPTIONAL EXTRAS

|   |
|---|
| Various output cable lengths              |
| Croc Clips                                |
| Various Connectors                        |
| 25A, 50A, 75A or 100A 28V DC power supply |



### RBL2500 14/28

|                      |  |
|----------------------|--|
| Max amps 28V         | 1300 (Nom. short circuit current)<br>2500 (Max. short circuit current)   |
| Max amps 14V         | 2600 (Nom. short circuit current)<br>5000 (Max. short circuit current)   |
| Capacity 28V         | 16 Amp Hrs @ 10 hr rate  |
| Capacity 14V         | 32 Amp Hrs @ 10 hr rate  |
| Max Voltage          | 28V DC   |
| Size (cm)            | L 40 x W 23 x H 21   |
| Weight kg            | 11   |
| Operating Temp.      | -40°C - +60°C  |
| Case                 | Stainless steel  |
| Voltage indication   | Digital to IP65  |
| Auxiliary Protection | Circuit breaker 40A  |
| Output Cable         | 2m heavy duty cable with aircraft connector                              |
| Charger              | 8 Amp Electronic fixed AC input charger. Charging time less than 2 hours |
| Protection           | Reverse polarity warning   |

- 12V/24V switchable
- Totally weather protected.
- Air transportable, 'Non Hazardous'
- Maintenance free.
- Tough and compact.
- No memory effect.
- Works in any orientation.
- High charge retention.
- Long shelf life.
- Fast recharge.
- No cycling.
- Leak proof.
- Cells replaceable on condition.
- Lightweight portable start power at remote locations.
- External charger for prolonged unit life.

[www.redboxpower.com](http://www.redboxpower.com) [sales@redboxpower.com](mailto:sales@redboxpower.com)

Tel (0) +44 1794 518888 Fax +44 (0) 1794 518848