

## Connection Systems

# MODEL TC3000/300-6

## High power, multiple start and continuous DC power unit

Our TC3000A range is simply a combination between our battery powered start units and our mains powered continuous power supply units.

When plugged into the mains these units will supply up to 600 amps continuously (dependent on the model). When unplugged they will give up to 7000 peak amps (dependent on the model).

- · Weather protected
- Air transportable, 'non-hazardous'
- Maintenance free
- Tough and compact
- No memory effect
- · High charge retention
- Long shelf life
- Fast recharge
- External charger for prolonged unit life
- No cycling
- · Leak proof
- Cells replaceable on condition
- Multiple heavy duty engines starting of turbo prop, turbine, aircraft and helicopters
- Continuous 28VDC power supply
- Starts main battle tanks
- Starts armoured fighting vehicles



#### **OPTIONAL EXTRAS**

Trailer	
Cable horns	
Various output cable lengths	
Various connectors	

#### **PROTECTION**

Overload
Over voltage
Over current
Short circuit
30mA RCD
Thermal management

PLUG SELECTOR	1 PHASE	3 PHASE
UK	240V 63 amps	16 amps
USA	N/A	@208V 32 amps, @480V 16 amps
Other countries	State country when ordering	State country when ordering

### TC3000/300-6 SPECIFICATION

Maximum	5000A (nom. short circuit current) 7800A (max. short circuit current)	
Capacity	114 amps hrs @ 10 hr rate	
Max start voltage	26VDC	
Continuous voltage	28.5VDC	
Continuous power	300 amps	
AC input	95V to 270V (3Ø available)	
Size with castors (mm)	L 905 x W 703 x H 766	
Weight nom (KG)	215	
Operating temperature	-40°C to +60°C	
Case	Zinc coated steel	
Voltage indication	LED display	
Performance monitoring	LED display	
Output cable	3m heavy duty cable with aircraft connector	
Charger	300 amp electronic inbuilt	
	Charging time less than 1 hour from 50%	

