

Connection

Systems

MODEL TC400A-28T

High powered, continuous and multi start battery unit

The TC400/28 range is designed to give silent, clean power. These 28V DC power supplies can offer both continuous power for a set time, and start power. With a built in 'flashing' light, the units will tell you when it is time to charge them. They also come with a built on voltmeter and an external charger that allows you to leave them on charge when not in use, ensuring they are always ready for operation. The TC400/28 range is designed specifically for when mains power is not readily available. They are maintenance free, with no moving parts, which make these units an extremely cost effective and environmentally friendly option.

www.lpa-group.com

www.redboxaviation.com

TC400A-28T SPECIFICATION

Maximum	7000A (nom. short circuit current) 10400A (max. short circuit current)
Capacity	272 amp hrs
Run time	190 amps for 1 hour, 110 amps for 2 hours, 78 amps for 3 hours etc
Max voltage	30.3VDC
Size (cm)	L 200 x W 108 x H 150
Weight (KG)	400
Operating temperature	-40°C to +60°C
Case	Zinc coated steel
Voltage indication	Digital to IP65
Auxiliary protection	Circuit breaker 40A
Output cable	3m heavy duty cable with aircraft connector
Charger	50 amp electronic 110/230V
	Charging time less than 4 hours from 50% (larger chargers available)



 Totally weather protected
• Air transportable, 'non-hazardous'
Maintenance free
 Tough and compact
 No memory effect
High charge retention
 Long shelf life
Fast recharge
• External charger for prolonged unit life
No cycling
Leak proof
Cells replaceable on condition
 Multiple heavy duty engine starting

OPTIONAL EXTRAS

Cable horns

Longer output cables



enquiries@lpa-connect.com +44(0) 1799 512800 www.lpa-group.com www.redboxaviation.com Light & Power House Shire Hill Saffron Walden, Essex CB11 3AQ, UK

Specification may change without notice

REV-04-24-1