

MODEL TC400A-6

High capacity, multiple start power unit for aircraft combat vehicles

Connection Systems

www.lpa-group.com

www.redboxaviation.com

- Totally weather protected
- Air transportable, 'non-hazardous'
- Maintenance free
- Tough and compact
- · No memory effect
- High charge retention
- Long shelf life
- · Fast recharge
- External charger for prolonged unit life
- · No cycling
- Leak proof
- Cells replaceable on condition
- Multiple heavy duty engines starting of turbo prop, turbine, aircraft and helicopters
- Starts main battle tanks
- Starts armoured fighting vehicles
- Portable start power at remote locations

SUPPLIED WITH UNIT

Charger

Output cable

OPTIONAL EXTRAS

Towbar

Handlebar and casters

Various output cable lengths

Various connectors



TC400A-6 SPECIFICATION

Maximum	5000A (nom. short circuit current) 7800A (max. short circuit current)
Capacity multiple start	114 amp hrs
Max voltage	26VDC
Size (cm)	L 78 x W 35 x H 30
Weight (KG)	135
Operating temperature	-40°C to +60°C
Case	Zinc coated steel
Voltage indication	Digital to IP65
Auxiliary protection	Circuit breaker 40A
Output cable	3m heavy duty cable with aircraft connector
Charger	20 amp electronic 110/230V
	Charging time less than 2 hours from 50%

