

MODEL TWIN RB75A

Hand and air portable power unit for aircraft and combat vehicles

Connection Systems

www.lpa-group.com

www.redboxaviation.com

- Totally weather protected
- Air transportable, 'non-hazardous'
- Maintenance free
- Tough and compact
- No memory effect
- Works in any orientation
- High charge retention
- · Long shelf life
- Fast recharge
- No cycling
- · Leak proof
- Cells replaceable on condition
- Heavy duty engine starting of turbo prop, turbine, aircraft and helicopters
- Starts main battle tanks
- Starts armoured fighting vehicles
- Lightweight portable start power at remote locations
- External charger for prolonged unit life

SUPPLIED WITH UNIT

2x charger

Output cable

Parallel joining cable

Twin trolley

2 x thermal protection bag

OPTIONAL EXTRAS

Various output cable lengths

Croc clips

Various connectors

25A, 50A, 75A or 100A 28VDC power supply



TWIN RB75A SPECIFICATION

Max amps	3500 (nom. short circuit current) 5200 (max. short circuit current)
Capacity	76 amps hrs @ 10 hr rate
Max voltage	26VDC
Size (cm)	2X L 45 x W 10 x H 38
Weight (KG)	70
Operating temperature	-40°C to +60°C
Case	Stainless steel
Voltage indication	Digital to IP65
Auxiliary protection	Circuit breaker 40A
Output cable	2m heavy duty cable with aircraft connector
Charger	2 x 8 amp electronic universal AC input
	Charging time less than 2 hours from 50%
Protection	Reverse polarity warning

