



REDBOX
INTERNATIONAL

TC3000/150-6

MODEL TC3000/150-6

HIGH POWER, MULTIPLE START AND CONTINUOUS DC POWER UNIT

(NSN 6130-99-815-2635)



SUPPLIED WITH UNIT

Output Cable

OPTIONAL EXTRAS

Towbar

Handlebar and Casters

Various Output Cable Lengths

Various Connectors

- *Weather protected.*
- *Air transportable, 'Non Hazardous'*
- *Maintenance free.*
- *Tough and compact.*
- *No memory effect.*
- *High charge retention.*
- *Long shelf life.*
- *Fast recharge.*
- *No cycling.*
- *Leak proof.*
- *Cells replaceable on condition.*
- *Multiple, heavy duty engine starting of turbo prop, turbine, aircraft and helicopters.*
- *Continuous 28V DC power supply*
- *Starts Main Battle Tanks.*
- *Starts Armoured Fighting Vehicles.*
- *Portable start power at remote locations.*

TC3000/150-6

Max amps	5000 (Nom. short circuit current) 7800 (Max. short circuit current)
Capacity	114 Amp Hrs @ 10 Hr rate
Max Start Voltage	26V DC
Continuous voltage	28.5v DC
Continuous power	150 amps
AC input	95v - 270v (3Ø Available)
Size (cm)	L89 W78 H46
Weight nom kg	165
Operating Temp	-40°C - +60°C
Case	Zinc Coated Steel
Voltage indication	LED display
Performance monitoring	LED display
Output Cable	3m heavy duty cable with aircraft connector
Charger	150A Electronic inbuilt. Charging time less than 30min from 50%.

Specification may change without notice

Plug Selector

	1Ph	2Ph
UK	240V 32A	3Ph 16A or 32A
USA	220V 20A or 30A	3Ph 20A or 30A with neutral
Other Countries	Please state country when ordering	Please state country when ordering

PROTECTION

- *Overload.*
- *Over Voltage.*
- *Over Current.*
- *Short Circuit.*
- *30mA RCD.*
- *Thermal Management.*



www.redboxint.com sales@redboxint.com

Tel +44 (0) 1794 518888 Fax +44 (0) 1794 518848