



MODEL TC3000/600/6

High power, multiple start and continuous DC power unit



Key Features and Benefits

- Totally Weather protected
- Maintenance free
- Tough and compact
- No memory effect
- High charge retention
- Long shelf life
- Fast recharge
- External charger for prolonged unit life
- No cycling
- Leak proof
- Cells replaceable on condition
- Multiple heavy duty engine starts
- Continuous 28VDC power supply



OPTIONAL EXTRAS

Trailer
Cable horns
Various output cable lengths
Various connectors

PROTECTION

Overload
Over voltage
Over current
Short circuit
30mA RCD
Thermal Management

TC3000/600/6 SPECIFICATION

Max amps	7800 amps
Starting amps	5200 amps
Capacity	114 amps hrs @ 10 hr rate
Starting voltage	24VDC
Max start voltage	26VDC
Continuous voltage	28VDC
Continuous power	600 amps
AC Input	200v-460v 3Ø
Size with castors (cm)	L 131 x W 66 x H 80
Weight (kg)	306
Operating temperature	-40°C- +60°C
Case	Zinc coated steel
Voltage indication	LED display
Performance monitoring	LED display
Aircraft Cable	3m heavy duty
Charger	600A electronic inbuilt. Charging time less than 30 mins from 50%
Optional	Towbar

PLUG SELECTOR

UK	16 amps
USA	208V 32 amps, 480V 16 amps
Other countries	State country when ordering



Specification may change without notice
REV-0-24-1



redbox@lpa-group.com
+44(0) 1799 512800
www.lpa-group.com
www.redboxaviation.com

Light & Power House
Shire Hill
Saffron Walden, Essex
CB11 3AQ, UK