



MODEL TC400/28C

High powered, continuous and multi start battery unit



Key Features and Benefits

- Totally Weather protected
- Maintenance free
- Tough and compact
- No memory effect
- High charge retention
- Long shelf life
- Fast recharge
- External charger for prolonged unit life
- No cycling
- Leak proof
- Cells replacable on condition
- Multiple heavy duty engine starts
- Continuous 28VDC power supply



OPTIONAL EXTRAS

Towbar
Handlebar and casters
Various output cable lengths
Various connectors

PLUG SELECTOR

UK	16 amps
USA	208V 32 amps, 480V 16 amps
Other countries	State country when ordering

TC400/28C SPECIFICATION

Max amps	5200 amps
Starting amps	3500 amps
Capacity	120 amps hrs @ 10 hr rate
Run time	82 amps for 1 hour 55 amps for 2 hours 27 amps for hours
Voltage	28VDC
Max voltage	30.3VDC
Size (cm)	L 101 x W 58 x H 39
weight (kg)	175
Operating temperature	-40°C- +60°C
Case	Zinc coated steel
Voltage indication	Digital to IP65
Auxiliary protection	Circuit breaker 40A
Aircraft Cable	3m heavy duty with connector
Charger	20A electronic 110/230V. Charging time less than 4 hours from 50% (larger charges available)
Optional extras	Cable extension



Specification may change without notice
REV-0-24-1



redbox@lpa-group.com
+44(0) 1799 512800
www.lpa-group.com
www.redboxaviation.com

Light & Power House
Shire Hill
Saffron Walden, Essex
CB11 3AQ, UK