



MODEL TC400/28TR

High powered, continuous and multi start battery unit



Key Features and Benefits

- Totally Weather protected
- Maintenance free
- Tough and compact
- No memory effect
- High charge retention
- Long shelf life
- Fast recharge
- External charger for prolonged unit life
- No cycling
- Leak proof
- Cells replacable on condition
- Multiple heavy duty engine starts
- Continuous 28VDC power supply



OPTIONAL EXTRAS

Cable horns

Longer output cables

PLUG SELECTOR

UK	16 amps
USA	208V 32 amps, 480V 16 amps
Other countries	State country when ordering

TC400/28TR SPECIFICATION

Max amps	15600 amps
Starting amps	10500 amps
Capacity	360 amps hrs @ 10 hr rate
Run time	245 amps for 1 hour 140 amps for 2 hours 100 amps for hours
Voltage	28VDC
Max voltage	30.3VDC
Size (cm)	L 130 x W 62 x H 71
weight (kg)	500
Operating temperature	-40°C- +60°C
Case	Zinc coated steel
Voltage indication	Digital to IP65
Auxiliary protection	Circuit breaker 70A
Aircraft Cable	3m heavy duty with connector
Charger	50A electronic 110/230V. Charging time less than 4 hours from 50% (larger charges available)
Optional extras	Cable extension



Specification may change without notice
REV-0-24-1



redbox@lpa-group.com
+44(0) 1799 512800
www.lpa-group.com
www.redboxaviation.com

Light & Power House
Shire Hill
Saffron Walden, Essex
CB11 3AQ, UK