



MODEL RBSC200 14/28V

Portable DC power supply with continuous 200 amp output

A compact, lightweight and highly portable power unit. Designed to give continuous high quality DC power for crew training, aircraft servicing in workshops, on the ramp or in the field. This continuous high power model is ideal for diagnostic work, pre flight checks, charging the on board battery or for continuous powering of equipment during operations, without draining the onboard aircraft batteries. There is a range of built in safety features and the units are simple to use. As standard the units will produce a steady 14.4 or 28.8 Volts up to the fully rated output current with power factor correction.



The power supplies are multi fan cooled with inbuilt thermal management for operation up to 50°C ambient environments. The safety features include; Internal AC Residual Current Protection, Overload and Short Circuit protection. The power modules conform to EMC standards for noise emissions and immunity. Delivered as standard this unit is supplied with a 2m heavy duty lead, fitted with a 3 pin NATO connector for direct aircraft connection, but extra extension and alternative format connections are available.

FEATURES

- Direct connection to aircraft or land vehicle
- Aircraft cable available from 2m to 6m
- Rugged lightweight aluminium case
- RCD safety protection
- Digital display with backlite - volts / amps / input status
- Multi fan cooled - temperature controlled
- Both input and output cables removable for easy stowage
- Supplied with input cable to required length
- Several options of output cable length and connections
- User switchable between 14V and 28V

PROTECTION

- Output overload
- Over voltage / current limit
- Short circuit
- 30mA RCD
- Advanced energy saving thermal fans

SAFETY & EMC

- Emissions: EN 55032 class A, EN 61000-3-2
- Immunity: EN 61000-4-2, EN 61000-4-3
- Safety: IEC 62368-1 (2014)

DIGITAL DISPLAY



RBSC200 SPECIFICATION

Output current	200 amps at above 180 VAC supply Auto reduction to 120 amps below 180 VAC
Output voltage	14.4V or 28.8VDC Auto 2 stage - pro mode, trimmable from 27.6 to 30 VDC
Output quality	Accuracy \pm 0.15 Volts – Ripple less than \pm 150m
AC input supply	95 to 264 VAC
AC input frequency	47 to 63 Hz
Phase	1Ø
Power factor	0.98/0.95
Input rating	6000VA
Operating temperature	-20°C to +50°C
IP rating	55* for use on level ground
Dimension (mm)	510 x 220 x 360 with integral handle
Weight (KG)	16 (unit only)

PLUG SELECTOR

UK plug selector	220VAC 32 amp standard
USA plug selector	115 VAC 30 amp NEMA 5-30 (30 amp) or 220 VAC 30 amp NEMA 6-30
Other countries	Please state country when ordering



SINCE 1861

redbox@lpa-group.com
+44(0) 1799 512800
www.lpa-group.com
www.redboxaviation.com

Light & Power House

Shire Hill
Saffron Walden, Essex
CB11 3AQ, UK

Specification may change without notice

REV-04-24-1