



Innovation Through Inspiration

MODEL TC400/28

High capacity, multiple start power unit for aircraft combat vehicles

www.lpa-group.com

www.redboxaviation.com

- Totally weather protected
- Air transportable, 'non-hazardous'
- Maintenance free
- Tough and compact
- No memory effect
- High charge retention
- Long shelf life
- Fast recharge
- External charger for prolonged unit life
- No cycling
- Leak proof
- Cells replaceable on condition
- Multiple heavy duty engines starting of turbo prop, turbine, aircraft and helicopters
- Portable start power at remote locations

SUPPLIED WITH UNIT

Charger

Output cable

OPTIONAL EXTRAS

Towbar

Handlebar and casters

Various output cable lengths

Various connectors



TC400/28 SPECIFICATION

Maximum	3500A (nom. short circuit current) 5200A (max. short circuit current)
Capacity multiple start	120 amps hrs (10 hour rate)
Max voltage	30.3VDC
Size (mm)	L 780 x W 540 x H 300
Weight (KG)	140 to 165
Operating temp	-40°C to +60°C
Case	Zinc coated steel
Voltage indication	Digital to IP65
Auxiliary protection	Circuit breaker 70A
Output cable	3m heavy duty cable with aircraft connector
Charger	50 amp electronic 110/230V Charging time less than 2 hours from 50%



SINCE 1861

redbox@lpa-group.com
+44(0) 1799 512800
www.lpa-group.com
www.redboxaviation.com

Light & Power House
Shire Hill
Saffron Walden, Essex
CB11 3AQ, UK

Specification may change without notice

REV-03-25-2