



Innovation Through Inspiration

# MODEL RB25 24V

Hand and air portable power unit for aircraft and combat vehicles

[www.lpa-group.com](http://www.lpa-group.com)

[www.redboxaviation.com](http://www.redboxaviation.com)

- Totally weather protected
- Air transportable, 'non-hazardous'
- Maintenance free
- Tough and compact
- No memory effect
- Works in any orientation
- High charge retention
- Long shelf life
- Fast recharge
- No cycling
- Leak proof
- Cells replaceable on condition
- Starts piston engine aircraft
- Lightweight portable start power at remote locations
- External charger for prolonged unit life



NSN 2995-99-132-3061

## RB25 SPECIFICATION

Max amps	800 (nom. short circuit current) 1300 (max. short circuit current)
Capacity	16 amps hrs @ 10 hr rate
Max voltage	26VDC
Size (cm)	L 35 x W 9 x H 23
Weight (KG)	16
Operating temperature	-40°C to +60°C
Case	Stainless steel
Voltage indication	Digital to IP65
Auxiliary protection	Circuit breaker 20A
Output cable	2m heavy duty cable with aircraft connector
Charger	2.5 amp electronic fixed AC input charger Charging time less than 2 hours
Protection	Reverse polarity warning

## SUPPLIED WITH UNIT

Charger

Output cable

Carry bag

## OPTIONAL EXTRAS

Various output cable lengths

Croc clips

Various connectors

25A, 50A, 75A or 100A 28VDC power supply



SINCE 1861

[redbox@lpa-group.com](mailto:redbox@lpa-group.com)  
+44(0) 1799 512800  
[www.lpa-group.com](http://www.lpa-group.com)  
[www.redboxaviation.com](http://www.redboxaviation.com)

Light & Power House  
Shire Hill  
Saffron Walden, Essex  
CB11 3AQ, UK

Specification may change without notice

REV-04-24-1