



MODEL Twin RBL4000 28V

Hand and air portable power unit for aircraft



Key Features and Benefits

Totally Weather protected

Maintenance free

Tough and compact

No memory effect

Works in any orientation

High charge retention

Long shelf life

Fast recharge

No cycling

Leak proof

Cells replaceable on condition

Heavy duty engine starting of turbo prop and turbine aircraft/helicopters

Lighweight portable start power at remote locations

External charger for prolonged unit life



SUPPLIED WITH UNIT

2x Charger
Output cable
Parallel joining cable
2x thermal protection bag

OPTIONAL EXTRAS

Twin trolley
Various output cable lengths
Croc clips
Various connectors
Carry case available

TWIN RBL4000 SPECIFICATION

Max amps	8000 amps
Starting amps	3000 amps
Capacity	56 amps hrs @ 10 hr rate
Voltage	28VDC
Max voltage	30VDC
Size (cm)	2 x L 35 x W 10 x H 38
Weight (kg)	24
Operating temperature	-30°C- +60°C
Case	Aluminium
Voltage indication	Digital to IP65
Auxiliary Protection	Circuit breaker 40A
Aircraft Cable	2m heavy duty, NATO connector
Charger	2x 4A electronic fixed input charger
Protection	Reverse polarity warning

PLUG SELECTOR

UK plug selector	240V 13 amp (standard mains)
USA plug selector	110V 15 amp (standard mains)
Other countries	Please state country when ordering



Specification may change without notice
REV-0-24-1



redbox@lpa-group.com
+44(0) 1799 512800
www.lpa-group.com
www.redboxaviation.com

Light & Power House
Shire Hill
Saffron Walden, Essex
CB11 3AQ, UK